

# Used Superior 36" x 80' Portable Radial Stacking Conveyor Unit #1105

#### #SN 1848565

#### **Conveyor Frame**

Main frame - 30" deep truss

Chord angles - 3" x 3" x 1/4", Bottom Chord upsized between pinpoints to 4" x 3" x 1/2"

Lattice members - 1 1/2" x 1 1/2" x 3/16"

## **Drive specifications**

Drive - Class I head end

Gear reducer - Dodge shaft mount

Backstop - installed in reducer

Motor - 30 HP 1800 RPM TEFC

V-belt drive - with drive guard

Capacity - 750 STPH of 100 PCF material, 25 degree surcharge (90% fines, 10% spherical lumps 7" minus)

Belt speed - 400 fpm

Superior pulleys

Drive pulley - 18" diameter, 3/8" herringbone lagged drum

Tail pulley - 16" diameter, CEMA Chevron® wing pulley

Head pulley - not applicable

Shafts - Turned and polished

Bearings - Dodge

Take ups - Screw type

### **Portability**



Conveyor splice - manual top folding head section

Undercarriage - Manual raise with pin lock adjustment

Axle type - Telescoping axle

Transport axle - Dual (4) 11R-22.5 tires and wheels

Radial axle - manual swivel boxes

Radial travel - manual

Fifth wheel - for road travel, bolt on design

Anchor pivot - maintains tail end during radial travel, for 5th wheel

Brakes - air brakes, complete system

Lights - brake and directional signals

Mud flaps - installed behind transport wheels

\*Axle jacks - not included

Landing gear - manual pin adjustment

Towing eye - Pintle type hitch

#### **Conveyor Components**

Belting - 3 ply 3/16 x 1/16 330 PIW

Belt splice - Flexco mechanical steel fasteners

Scraper - not included

Superior Idlers - CEMA C, 5" dia. rolls, sealed for life ball bearings

Load area - 20° trough, 12-16" spacing

Trough - 35° on 4' spacing

Returns - steel rolls, on 10' spacing

Radial hopper - sloped, 5' long, bolt on design

Gathering trough - 5' long with adjustable rubber flashing



# **Additional Specifications**

Guarding - for drive and tail pulleys, v-belt drive and return idlers. Guards may not meet all local codes; customer is responsible to have guarding inspected.

Voltage - 480 v / 3 ph / 60 hz

Cord Holders - (1) Set bent pipe style

Electrical - Control panel and wiring included

Panel mount - Not included

Paint - 1 coat primer, 1 coat finish enamel

Idler Paint - powder coated Superior Orange

Owner's Manual - (1) copy in English included for operation and maintenance























