

Superior 36x40 Portable Radial Stacking Conveyor Unit #1372

#SN 2309826

Equipment As Follows:

- Conveyor Frame
- Main Frame-24" deep truss
- Chord Angles-3" x 3" x 1/4"
- Lattice Members-1-1/2" x 1-1/2" x 3/16"
- Containerized-not included
- **Drive Specifications**
- Drive-Class I head drive
- Gear Reducer-Shaft Mount
- Backstop-installed in reducer
- Motor-15 HP TEFC
- V-Belt Drive-with drive guard
- Capacity-750 STPH of 100 PCF material, 25° surcharge (90% fines, 10% spherical lumps, 6" minus)
- Belt Speed-400 fpm
- Drive Pulley-16" diameter, 3/8" herringbone lagged drum
- Tail Pulley-14" diameter, CEMA Chevron® wing
- Shafts-Turned and Polished
- Bearings-Included
- Take-up-Screw type
- Portability



| Conveyor Splice-one piece frame |
|--|
| Undercarriage-manual raise with pin lock adjustment |
| Axle Type-fixed width axle, road portable |
| Transport Axle-Single 11R-22.5 tires and wheels |
| Radial Axle-manual swivel boxes |
| Radial Travel-manual |
| Fifth Wheel-for road travel, bolt on design |
| Anchor Pivot-maintains tail end during radial travel, for 5th wheel |
| Brakes-not included |
| Lights-brake and directional signals |
| Mud Flaps-not included |
| Axle Jacks-not included |
| Landing Gear-manual pin adjustment |
| |
| Towing Eye-pintle hitch type |
| Towing Eye-pintle hitch type |
| Towing Eye-pintle hitch type Conveyor Components |
| |
| Conveyor Components |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners Scrapers-Superior Exterra® Primary Belt Scraper |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners Scrapers-Superior Exterra® Primary Belt Scraper Idlers-CEMA C, 5" dia. Steel rolls, sealed for life ball bearings |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners Scrapers-Superior Exterra® Primary Belt Scraper Idlers-CEMA C, 5" dia. Steel rolls, sealed for life ball bearings Idler Seal-Superior Standard SpinGuard® Seal |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners Scrapers-Superior Exterra® Primary Belt Scraper Idlers-CEMA C, 5" dia. Steel rolls, sealed for life ball bearings Idler Seal-Superior Standard SpinGuard® Seal Load Area-20° trough, 12-16" spacing |
| Conveyor Components Belting-3-ply 3/16 x 1/16 330PIW Belt Splice-Flexco mechanical steel fasteners Scrapers-Superior Exterra® Primary Belt Scraper Idlers-CEMA C, 5" dia. Steel rolls, sealed for life ball bearings Idler Seal-Superior Standard SpinGuard® Seal Load Area-20° trough, 12-16" spacing Trough-35° on 4' spacing |



Gathering Trough-5' long with adjustable rubber flashing

Additional Specifications

Guarding-For drive and tail pulleys, v-belt drive and return idlers. Guards may not meet all local codes; customer is responsible to have guarding inspected

Voltage-480 V / 3 PH / 60 Hz

Cord Holders-(1) set bent pipe style

Control Panel Plate-not included

Control Panel-control panel and wiring not included

Paint-1 coat primer, 1 coat finish enamel (*available colors below)

Guard Paint

Idler Paint-Powder coated Superior Orange

Owner's Manual-(1) copy in English included for operation and maintenance

On-Site Start-up, Training and Warranty Commissioning

• RB Scott will supply a field service technician to complete startup









