

Straightline 42x125 Portable Radial Stacking Conveyor Unit #1339

#421250223780

Equipment As Follows:

- Frame: Tail section 4 x 4 x 5/16 chord angles, 2 x 2 x 1/4 angle lattice, Mid & Head section 4 x 4 x 1/4 chord angles, 2 x 2 x 1/4 angle lattice members with 5 x 3 x 5/16 angle for bottom extra cord
- 15Hp electrical hydraulic power unit
- Hydra-fold on head and tail section
- Hydraulic adjustable height undercarriage
- SLI Fold Down series axle
- (4) 385/65R-22.5 tires on out rigger
- (4) 2hp Planetary drives for radial travel
- Tandem Axle with – (8) 11.00R /22.5 tires
- Air Brake package, light package, Mud Flaps
- 24" x 44" Drive pulley with 3/8" lagging – 4 7/16" shaft
- 16" x 44" Head pulley - 3-15/16" shaft
- 24" x 44" Wrap pulley - 3-15/16" shaft
- 16" x 44" Tail wing pulley – 3-15/16" shaft
- CEMA C – Troughing idlers 5" rollers on 4' centers
- CEMA C - Return idlers 5" rollers on 10' centers
- Gear Reducer: Master PT size 8 with backstop
- Motor: 60hp 1800 230/460/3ph
- Electrical: Switch gear with 60hp and 15hp starter with 100ft extra cord
- Bearings: Dodge S2000
- 980TPH / 350FPM
- Take-ups: Top Angle
- Conveyor belt: 42"- 3 ply 3/16 x 1/16" cover
- Vulcanized belt splice
- 5' receiving hopper with extra idlers at load point
- Holland heavy duty landing gear
- Fifth wheel hitch and tow eye
- Pivot plate
- Belt Cleaner: By Superior
- Guarding: Tail pulley and V-belts
- Sandblasted: Frame
- (1) Coat primer urethane (1) Coat finished urethane

On-Site Start-up, Training and Warranty Commissioning

- RB Scott will supply a field service technician to complete startup



