

Straightline 36x60 Pit Portable Radial Stacking Conveyor Unit #1236

#36600223779

- Frame: : 3 x 3 x 1/4" Chords with 2 x 2 x 3/16" Lattice members – with 3 x 3 x 3/16" angle recessed in frame for troughing idlers
- 24" Deep Truss
- SLI V-style adjustable height under carriage – manual pin adjustment
- Axle: Single Fixed w/single 11.00-22.5 tires with swivel plates for manual radial travel
- Head pulley: 14" x 38" C.F. – 3/8" H.B. lagging – 2-15/16" shaft
- Tail pulley: 12" x 38" Wing style – 2-7/16" shaft
- Troughing idlers: CEMA B – 5" rollers on 4' centers
- Return idlers: CEMA B– 5" rollers on 10' centers
- Return idler nip guards
- Gear Reducer: Master PT size 5 with backstop
- Motor: 20HP 1800RPM 230/460/3ph Toshiba
- 750TPH / 400FPM
- Bearings: Dodge SCM
- Take-ups: SLI Screw Type
- Conveyor belt: 36"- 3 ply 3/16" x 1/16" cover
- Belt scraper: Superior
- 6' Radial receiving hopper with extra idlers at load point
- Radial Hopper with stake pockets (removable)
- Tow ring
- Guarding: Tail pulley and V-belts
- Sandblasted: Frame
- (1) Coat primer urethane (1) Coat finished urethane





