



Used 2017 Greystone 44in Single Sand Screw Unit #1273

#SN FM44S71129894GS

Screw Size- single 44" x 32' fine material screw

Lower Bearing- Dodge Imperial-E 3.9375" 4-bolt EP4B-IP-315R non-exp

Upper Bearing- Dodge S2000-E 3.9375" 4 bolt EP4B-S2-315RE expansion

Wear Shoe Type- 44" Rubber

Reducer- Dodge TA7315H40 TB / 39.66:1

Reducer Bushing- Dodge TA315TB x 3.9375"

Reducer Torque-Arm Mount- GS TA7-8

Reducer Torque-Arm- GS 7-8X21.28"

Reducer Motor Mount- GS TA7-8

V-belt Guard- GS TA7-8 #30

Screw Speed- 17 RPM

Motor HP/RPM/Frame- 20HP 1800RPM 256 T 3P/60HZ/230/460V TEFC

Motor Sheave Size- 2B 5.8 QD

Motor Sheave Bushing- SDS 1.625"

Reducer Sheave Size- 2B 15.4 QD

Reducer Sheave Bushing- SK 2.4375"

V-belt Type/Size- B-120 42.9"

Switchgear

Manifold

Discharge Chute

Support Legs

Large Feed Well

