

MDS M413 Mobile Trommel Unit #1563

#TRXMD413ECKS79741

Equipment As Follows:

The M413 Track Trommel is perfect for cleaning dirty material and can handle rocks up to 600mm (24") in size. It comes complete with fold out stockpiling conveyors and is ideal for moving around the quarry and from one site to another.

M1413

Fines - 4" replaceable panels to allow repair or replacement of individual sections

Mid-Product - 12" replaceable panels to allow repair or replacement of individual sections

Tipping Grid - 18"

Hopper and Feeder

Feed hopper capacity - 5.23yd3

Reciprocating Push Feeder

Hopper Extensions - Folding hopper extensions

Transport Dimensions

Transport Dimension (L x W x H) – 43'-11" x 8'-5" x 12'- 10" (tipping grid & chassis riser)

Working Dimension (L x W x H) - 55'-2" x 22'-0" x 11'- 5"

Weight with Chassis Riser

Unit with Grid – 57,997 lbs.

Conveyors

Fines Conveyor



	o,	O"	\ A /i	de
_	. 7 .		W	

- Discharge height 6'-6"

Mid Product Conveyor

- 4'-5" wide
- Discharge height 6'-6"

Oversize Conveyor

- 3'-3" wide
- Wide tough flex belt
- Discharge height 6'-8"

Drum

Diameter - 4'1"

Length - 13'1"

Incline - 5 degrees

Power Unit

Engine - CAT 2.2 55kW (73.76HP) Diesel Engine. Tier 4 Final/STAGE 5 Dual Certified

Electrical Control System

Heating- Hydraulic oil heater included

Hydraulic Oil & Lubrication

Standard - ISO Grade 46

Optional - Grade 68 (hot climates)



Chassis & Tracks

Heavy track undercarriage

Chassis Riser - Included

Control operation of tracks - via handheld-set with connection lead or wireless remote control

Telematics

T-Link Telemetry System fitted c/w 3 years Satellite and GSM data subscription, bundled deal with ancillary services

Paint

MDS standard Colors - Cream & grey

























