

GreyHawk Portable 36x70 Roll-Off Transfer Conveyors Unit 1593

Equipment As Follows:

1. CHASSIS

- Trailer Unit
- Mid/Top Units
 - 30" deep truss
 - 4"x4" chord angles
 - 2"x2" lattice members
 - Fifth wheel hitch
 - Tandem Axle (8) 11x22.5 radial tires
 - Air brakes
 - Kingpin support for transport
 - Mud flaps
 - Pintle hitch
 - Light bar

 - 30" deep truss
 - 4"x4" chord angles
 - 2"x2" lattice members
 - Rollers
 - Transport brackets
 - Adjustable head supports for operation/travel
 - Adjustable tail support tubes for operation/travel

1. DRIVE SPECIFICATIONS

- Class I drive package
- Master PT #5 gearbox
- Backstop
- WEG 25HP/1800RPM motor
- 350FPM belt speed
- 750TPH (based on 100PCF)

1. CONVEYOR COMPONENTS

- Superior 16" head pulley
- Superior 14" wing pulley
- Superior CEMA C 5" top mount idlers
- Superior CEMA C 5" return idlers

- Fold up receiving hopper
- Dodge SCM pillow block bearings
- Screw type take-ups
- 3-ply 3/16 belting
- Mechanical splice
- Argonics scraper
 - 20-degree trough in load zone
 - 35-degree trough, 4' spacing

1. ELECTRICAL

- Power supply-480v/3-ph/60hz
- Control panel for each conveyor
- Wiring from the control panel to the corresponding motor included
- Cable holders

1. SAFETY/GUARDING

- We install all standard guarding, customer will be responsible for compliance with local codes.

1. GENERAL:

- Paint
- (2) sets of owners/parts manuals
 - Sandblasted
 - Two-part epoxy primer
 - Two-part urethane topcoat
 - Chassis Color-GH Beige
 - Handrail/Guarding Color-GH Orange
 - Decals-Orange & grey striping



RBSCOTT

EQUIPMENT • WEAR PARTS • SERVICE

