

GreyHawk Portable 36x70 Roll-Off Transfer Conveyors Unit #1646

#1331

Equipment As Follows:

1. CHASSIS

- Trailer Unit
- 30" deep truss
- 4"x4" chord angles
- 2"x2" lattice members
- Fifth wheel hitch
- Tandem Axle (8) 11x22.5 radial tires
- Air brakes
- Kingpin support for transport
- Mud flaps
- Pintle hitch
- Light bar
- Mid/Top Units
- 30" deep truss
- 4"x4" chord angles
- 2"x2" lattice members
- Rollers
- Transport brackets
- Adjustable head supports for operation/travel
- Adjustable tail support tubes for operation/travel

1. DRIVE SPECIFICATIONS

- Class I drive package
- Master PT #5 gearbox
- WEG 20HP/1800RPM motor
- 350FPM belt speed
- 750TPH (based on 100PCF)

1. CONVEYOR COMPONENTS

- Superior 16" head pulley
- Superior 14" wing pulley
- Superior CEMA C 5" top mount idlers
- 20-degree trough in load zone
- 35-degree trough, 4' spacing
- Superior CEMA C 5" return idlers
- Fold up receiving hopper
- Dodge SCM pillow block bearings
- Screw type takeups
- 3-ply 3/16 belting
- Mechanical splice
- Argonics scraper

1. ELECTRICAL

- Power supply-480v/3-ph/60hz
- Control panel for each conveyor
- Wiring from the control panel to the corresponding motor included
- Cable holders

1. SAFETY/GUARDING

- We install all standard guarding, customer will be responsible for compliance with local codes.

1. GENERAL:

- Paint
- Sandblasted
- Chassis Color-GH Beige
- Guarding Color-GH Orange
- (1) sets of owners/parts manuals

