

Metso Lokotrack ST3.8 Mobile Screen, Unit #918

#79949

Feeding Unit

Feeder unit-Standard

- Hopper with belt feeder

Feeding unit type-Tipping grid

- Robust, heavy duty grid assembly. Variable working angle (19, 25, 30 Deg.). Radio remote control of hydraulic tipping grid.

Tipping grid-130 mm (5,1")

- Grid spacing 130 mm (5")

Screening Unit

Screening unit-ST3.8 two-deck screen

Power Unit

Diesel engine-CAT C4.4

Emission class-Tier 3

- Tier 3 (stage IIIA) emission regulated engine.

Climate kit-Standard (-20C/-4F...35C/95F)

Air Filters-Standard

Conveyors

Main conveyor-Standard

- Lifting conveyor to screen

Product conveyor-Standard

- Bottom deck undersize

Side conveyor, oversize-Standard

- Top deck oversize

Side conveyor, undersize-Standard

- Bottom deck oversize

Included Optional Equipment

Unit control type-with IC

Metso Metrics System-Included

- Remote monitoring and reporting system for Lokotrack. Consists of modem and antenna installation. Access to the monitoring and maintenance scheduling system and reporting services can be ordered with a separate service contract.

Remote radio control-Multifunction control (434MHz)

Screen Service platform-Three sided platforms & stairs

- Provides access to rear and to sides of screen.

Screen discharge chute-Standard + wear plate

Tool kit-Included

- Includes special tools required in maintenance operations.

Interlocking cable-Included

- Secondary unit material level will control the feeding of primary unit.

Hydraulic power take off (PTO)-Included

Main conveyor lifting-Included

- Hydraulic lifting cylinders for main conveyor. Easier screen mesh change.

Finishing

Color-Metso beige

Safety labels-ANSI

Display unit language-English

Documentation

Quantity of printed manuals-2

Electronic spare part book-Included

Quantity of spare part books-2

