

Straightline 36" x 60' Portable Transfer Conveyor, Unit #932

#36600119623

- Frame: 3 x 3 x 1/4" angle chords with 2 x 2 x 3/16" angle lattice members with 4 x 3 x 1/4" angle for extra chord
- Truss: 36" Deep
- Adjustable height under carriage – manual pin adjustment
- Axle: Single 11.00-22.5 tires
- Air brakes & Light package
- Head pulley: 16" x 38" C.F. – 3/8" H.B. lagging – 2-15/16" shaft
- Tail pulley: 14" x 38" Wing style – 2-7/16" shaft
- Troughing idlers: CEMA C – 5" rollers on 4' centers
- Return idlers: CEMA C – 5" rollers on 10' centers
- Gear Reducer: Dodge size 5
- Motor: 15HP 1800RPM 230/460/3ph Toshiba
- 800TPH / 350FPM
- Bearings: Dodge SCM
- Take-ups: SLI screw type
- Conveyor belt: 36"- 3 ply 3/1 cover
- Belt scraper: Superior
- 5' receiving hopper with extra idlers at load point
- Hitch: 5th wheel and tow eye
- Guarding: Tail pulley and V-belts
- Sandblasted: Frame
- (1) Coat primer urethane (1) Coat finished urethane
- Electrical panel with 100ft extra cord

